



Technical Service Information Bulletin

March 8, 2006

Title:

FRONT WHEEL OPENING EXTENSION PAD INSTALLATION DURING PDS

Models:

'07 ES 350

PD021-06

PRE-DELIVERY SERVICE

Introduction The front wheel opening extension pad set (right and left front wheel opening extension pads, 6 tapping screws) is loaded in the luggage compartment at the assembly plant to avoid damage in transit. Install the front wheel opening extension pads to the vehicle during Pre-Delivery Service (PDS) at the dealership prior to delivery to the customer.

Applicable Vehicles


- **2007** model year **ES 350** vehicles.

Installation Procedure

1. Remove the two (2) self-tapping screws from the engine under cover.

NOTE:


Discard the two (2) self-tapping screws. They will **NOT** be reused.



2. Place the left front wheel opening extension pad on the installation position and temporarily tighten the three (3) self-tapping screws.
3. Tighten the three (3) self-tapping screws.

NOTE:

- There is a distinguishable mark on each pad.
- Be sure to install the extension pads with the self-tapping screws supplied with the pads.



4. Repeat steps 2 – 3 to install the right front wheel opening extension pad.

**Warranty
Information**

OP CODE	DESCRIPTION	TIME	OFF	T1	T2
N/A	Not Applicable to Warranty	—	—	—	—



Lexus Supports ASE Certification