



Technical Service Information Bulletin

December 12, 2006

Title:

SMART KEY SPECIFICATIONS

Models:

'04 – '06 LS 430, '06 GS 300 & GS 430,
IS 250 & IS 350, & '07 ES 350 & GS 450h

ELECTRICAL
EL015-06

Introduction Some customers may inquire about the frequency and power output of the Smart Key/Smart Access systems used on various models. The Smart Key/Smart Access systems conform to all applicable FCC rules. This bulletin details the applicable specifications for these systems.

CAUTION:


Implanted pacemakers, cardiac defibrillators, or other electrical medical devices may be affected by radio waves emitted by the Smart Key/Smart Access Antenna (in detection area). Customers with concerns about these systems and their effects on implanted electronic medical devices should consult their physician or the device manufacturer. This information is also included in the Owner's Manual for each applicable model.

If necessary, details on disabling the Smart Key/Smart Access functions can be found in the appropriate vehicle Repair Manual. Refer to the Technical Information System (TIS) for additional details.

Applicable Vehicles

- **2004 – 2006** model year **LS 430** vehicles.
- **2006** model year **GS 300**, **GS 430**, **IS 250**, and **IS 350** vehicles.
- **2007** model year **ES 350** and **GS 450h** vehicles.

Smart Key Detection Area



Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
N/A	Not Applicable to Warranty	—	—	—	—



Lexus Supports ASE Certification

Specifications Smart Key Antenna (communication from vehicle to key):

- Frequency: 134.2 kHz
- Power Output: 94.2dB $\mu\text{V}/\text{m}$ (at 3 meters away from the Smart Key Antenna)
- Specifications for Smart Antenna RF Output Power:

	SPECIFICATION			
	FREQUENCY	OUTPUT POWER/ ELECTRIC FIELD INTENSITY	MODULATION METHOD	MOUNTING POINT IN VEHICLE
Inside Passenger Compartment	134.2 kHz	92dB $\mu\text{V}/\text{m}$ –3m	AM	Differs in each vehicle; consult the relevant Service Manual for each vehicle
Inside Trunk (ONLY in Vehicles w/Trunk)	134.2 kHz	92dB $\mu\text{V}/\text{m}$ –3m	AM	Inside Trunk
Outside Vehicle	134.2 kHz	92dB $\mu\text{V}/\text{m}$ –3m	AM	1)Inside Door Handle 2)Inside Rear Bumper

Specifications
(Continued)

	TRANSMIT TIMING		
	VEHICLE PARKED	ENTERING OR EXITING VEHICLE	VEHICLE IS BEING DRIVEN
Inside Passenger Compartment	Does NOT Transmit	<ul style="list-style-type: none"> Operating door locks Operating engine switch/depressing brake pedal Opening or closing doors With IG ON or ACC ON, and in the P-range, closing a door when the key cannot be detected inside the vehicle (continues for 3 seconds until the key is detected or the power switch is turned OFF), AT and HV vehicles ONLY IG OFF after driving more than 20 minutes (Not in P-range) when shutting the door, if the key cannot be detected inside the vehicle (transmits for 3 seconds until the key is located), AT and HV vehicles ONLY 	When key is NOT detected inside passenger compartment while car is being driven (transmits for 3 seconds)
Inside Trunk (ONLY in Vehicles w/Trunk)	Does NOT Transmit	During the following operations: <ul style="list-style-type: none"> Door lock is operated/trunk switch is depressed Closing the trunk Opening or closing doors 	Does NOT Transmit
Outside Vehicle	1)When door is locked, transmits at 250 ms intervals (stops when door is unlocked) 2)Does NOT transmit	1)Lock switch is depressed 2)Trunk or back door open switch is depressed	Does NOT Transmit

Smart Key Transmitter/Wireless Remote (communication from key to vehicle):

- Frequency: 312 – 315 mHz